

440.632.02

date of issue: 14-04-2014



Certificateholder  
Salto Systems SL  
Poligono Lanbarren C / Arkotz 9  
920180 Oiartzun  
T : +34 (0) 943 344 550  
F : +34 (0) 943 341 621  
E : info@saltosystems.com  
I : www.saltosystems.com



## Declaration of SKG

This certificate is in accordance with the SKG Regulations approval, product certification and process certification: 2011.

SKG declares that the by or on behalf of the certificate owner produced building hardware product:  
narrow plate with electro mechanical handle link

delivered under logo / brand:  
SALTO

delivered under type- and / or article number:  
Ei4K2 m 00 ff t x h r , Ei4K3 m 00 ff t x h r , Ei4K4 m 00 ff t x h r

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

## SKG

*bezoekadres*  
Nieuwe Kanaal 9F  
6709 PA Wageningen

*postadres*  
Postbus 362  
6700 AJ Wageningen

**T** 0317 - 421 720  
**F** 0317 - 421 677  
**E** info@skg.nl  
**I** www.skg.nl

For SKG

ir. H.A.J. van Dartel  
Certification manager

---

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.

---

This certificate has 2 pages

# SKG productcertificate

Salto Systems SL

Number: 440.632.02

page 2 of 2

---

## 1. PRODUCT

narrow plate with electro mechanical handle link

## MAIN GROUP

security furniture

---

## 2. TECHNICAL SPECIFICATION:

Construction: 1 set of an outside part and an inside part with mounting screws

Operating / System: for 17 mm cylinders; electro mechanical handle link, various handles

Material: outside part: inox with aluminium and zinc coated steel inside; inside part: zinc coated steel with inox cover

Dimension: outside- /inside part: 282x41x20 mm

Fixing: 3xM5 in steel cams

Intended use: in combination with mortice locks

---

## 3. DELIVERY

The delivery includes an installation instruction:

Alg: Intallation guide Ei45x... : 2011 55-ED. 22/11/2010 + SKG: Intallation guide Ei4Kxx... : 220744 -EDO -05/01/2011

---

## 4. PERFORMANCES

A narrow plate with electro mechanical handle link according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this narrow plate with electro mechanical handle link is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled. Remark: In façade elements in accordance with a burglar resistance class (RC) of EN 1627 only SKG\*\*\* cylinders are applicable.

A window or door, in existing buildings, in which this narrow plate with electro mechanical handle link is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-