

# SKG-IKOB PRODUCTCERTIFICATE

## 440.393.06

Date of issue: 29-11-2018



### Certificate holder

Salto Systems SL  
Poligono Lanbarren C / Arkotz 9  
920180 Oiartzun  
T: +34 (0) 943 344 550  
E: info@saltosystems.com  
I: www.saltosystems.com



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

### Europrofile cylinder single OR doubleelectro mechanical cylinder

delivered under logo / brand:

### SALTO

delivered under type- and / or article number:

### NBE1xxG , NBE3xxG

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script that appears to read "H.A.J. van Dartel".

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
[info@skgikob.nl](mailto:info@skgikob.nl)  
[www.skgikob.nl](http://www.skgikob.nl)

# SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL  
Number: 440.393.06

page 2 of 2

## 1. PRODUCT

Europrofile cylinder single OR double electro mechanical cylinder

## PRODUCT TYPE

cylinder

---

## 2. TECHNICAL SPECIFICATION

Operating:	Electronical operation
Construction:	single with a lockable knob double with on both sides a lockable knob modulair single with a lockable knob modulair double with on both sides a lockable knob
System:	knob with full length plug, coupled with de cam by electronic operation
Material:	cylinder body: brass with various coatings; with OR without steel bridge
Dimension:	17 mm profile from 30 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length $\geq$ backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furniture

---

## 3. DELIVERY

The delivery includes an installation instruction:  
225790-ED.- 15102018

---

## 4. PERFORMANCES

A Europrofile cylinder single OR double electro mechanical cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this Euro-profile cylinder, single OR double, electro mechanical cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this Euro-profile cylinder, single OR double, electro mechanical cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
-