

SKG-IKOB PRODUCTCERTIFICATE

440.393.06

Date of issue: 27-05-2024



Certificate holder

Salto Systems SL
Poligono Lanbarren C / Arkotz 9
920180 Oiartzun
T: +34 (0) 943 344 550
E: info@saltosystems.com
I: www.saltosystems.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

Europrofile cylinder electro mechanical

delivered under logo / brand:

SALTO

delivered under type- and / or article number:

**NME1xxG , NME3xxG , NJE1xxG , NJE3xxG
NMEAxxG , NJEAxxG , NMECxxG , NJECxxG**

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL
Number: 440.393.06

page 2 of 2

1. PRODUCT

Europrofile cylinder electro mechanical

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating:	Electronical operation
Construction:	single with a lockable knob double with on both sides a lockable knob modulair single with a lockable knob modulair double with on both sides a lockable knob
System:	knob with full length plug, coupled with de cam by electronic operation operation by: - Keycard, Fob or Wearable - SALTO KS mobile app. on phone or tablet
Material:	cylinder body: brass with various coatings with OR without steel bridge
Dimension:	17 mm profile from: (single) 10/30 mm and (double) 30/30 mm in various extensions per 5 mm possibly with extended plug of +5 OR +10 mm
Fixing:	1 steel bolt M5, length \geq backset + 10 mm
Intended use:	The electromechanical product is operated electronically using the options stated under "System". The operating options listed below, as well as the closure, are included in the Self-declaration - additional product requirements for electromechanical and electronic hinges and locks; dated 08-01-2024, with which the certificate holder declares that the applicable requirements are met. in combination with cylinder mortise locks and security furniture The modular cylinder can be assembled by the customer onsite to adapt to the thickness of the door, the exterior cylinder subassembly with a body of 30 mm (Ni0EkkfG) in a box and the rest of the parts in a briefcase (SPKNEOM1).

3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

225790-ED.1- 12/09/2023

227823 -ED0 -23/05/2023

4. PERFORMANCES

A Europrofile cylinder electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this Euro-profile cylinder, electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this Euro-profile cylinder, electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).