

# SKG-IKOB PRODUCTCERTIFICATE 440.393.07

Date of issue: 21-10-2023



## Certificate holder

Salto Systems SL  
Poligono Lanbarren C / Arkotz 9  
920180 Oiartzun  
T: +34 (0) 943 344 550  
E: info@saltosystems.com  
I: www.saltosystems.com



## Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

### europofile cylinder with non lockable knob electro mechanical

delivered under logo / brand:

### SALTO

delivered under type- and / or article number:

### NME2xxG , NME2xxAG , NJE2xxG , NJE2xxAG

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
[info@skgikob.nl](mailto:info@skgikob.nl)  
[www.skgikob.nl](http://www.skgikob.nl)

# SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL  
Number: 440.393.07

page 2 of 2

## 1. PRODUCT

europrofile cylinder with non lockable knob electro mechanical

## PRODUCT TYPE

cylinder

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electrical operation
Construction:	Euro-profile cylinder double, with on both sides knob, 1 side lockable, with OR without panic function modulair double with on both sides a turning knob, 1 side lockable, with OR without panic function
System:	knob with full length plug, coupled with de cam by 1 side electronic operation
Material:	cylinder body: brass with various coatings with OR without a steel bridge
Dimension:	17 mm profile from 30/30 mm in various extensions per 5 mm possibly with extended plug of +5 OR +10 mm
Fixing:	1 steel bolt M5, length $\geq$ backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furniture. Pay Attention! This cylinder achieves only the SKG-star rating if a door element (including side window), wherein at least P4A glass has been applied, OR in a door element (including side window) with a section filling without a view on the knob. A wooden door element (including side window) with a view to the "standard" turning knob, should be provided with a SKG (V) certified anti-drill / manipulation device.

## 3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

225790-ED.1 - 12-09-2023

225791-ED.1 - 12-09-2023

227823-ED0 - 23-05-2023

## 4. PERFORMANCES

A europrofile cylinder with non lockable knob electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro-profile cylinder with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this euro-profile cylinder with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).