

SKG-IKOB PRODUCTCERTIFICATE 440.393.07

Date of issue: 27-05-2024



Certificate holder

Salto Systems SL
Poligono Lanbarren C / Arkotz 9
920180 Oiartzun
T: +34 (0) 943 344 550
E: info@saltosystems.com
I: www.saltosystems.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

europofile cylinder with non lockable knob electro mechanical

delivered under logo / brand:

SALTO

delivered under type- and / or article number:

**NME2xxG , NME2xxAG , NJE2xxG , NJE2xxAG
NMEBxxG , NJEBxxG**

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive name followed by a horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL
Number: 440.393.07

page 2 of 2

1. PRODUCT

europrofile cylinder with non lockable knob electro mechanical

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating: Mechanical and electrical operation

Construction: Euro-profile cylinder
double, with on both sides knob,
1 side lockable, with OR without panic function
modulair double with on both sides a turning knob,
1 side lockable, with OR without panic function

System: knob with full length plug,
coupled with de cam by 1 side electronic operation

operation by:

- Keycard, Fob or Wearable
- SALTO KS mobile app. on phone or tablet

Material: cylinder body: brass with various coatings
with OR without a steel bridge

Dimension: 17 mm profile from 30/30 mm in various extensions per 5 mm
possibly with extended plug of +5 OR +10 mm

Fixing: 1 steel bolt M5, length \geq backset + 10 mm

Intended use: The electromechanical product is operated electronically using the options stated under "System".
The operating options listed below, as well as the closure, are included in the
Self-declaration - additional product requirements for electromechanical and electronic hinges and locks; dated
08-01-2024,
with which the certificate holder declares that the applicable requirements are met.

in combination with cylinder mortice locks and security furniture.

Pay Attention!

This cylinder achieves only the SKG-star rating if
a door element (including side window), wherein
at least P4A glass has been applied,
OR in a door element (including side window) with
a section filling without a view on the knob.
A wooden door element (including side window) with
a view to the "standard" turning knob, should be provided with
a SKG (V) certified anti-drill / manipulation device.

The modular cylinder can be assembled
by the customer onsite to adapt to the thickness of the door,
the exterior cylinder subassembly with a body of 30 mm (Ni0EkkfG)
in a box and the rest of the parts in a briefcase (SPKNEOM1).

3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

225790-ED.1 - 12-09-2023

225791-ED.1 - 12-09-2023

227823-ED0 - 23-05-2023

4. PERFORMANCES

A europrofile cylinder with non lockable knob electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this euro-profile cylinder with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL
Number: 440.393.07

page 3 of 2

A window or door, in existing buildings, in which this euro-profile cylinder with non lockable knob, electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
